



Dimensions are in millimeters and include label.

Chemical system:	Nickel-Metal Hydride		
Designations:	IEC HR6, ANSI 1.2H2		
Nominal Voltage:	1.2V		
Nominal Capacity:	1700 mAh	2500 mAh	2600 mAh
Rated, Minimum Capacity: (IEC/EN 61951-2)	1600 mAh	2400 mAh	2500 mAh
Charging Condition:	170 mA for 16h	250 mA for 16h	260 mA for 16h
Maximum continuous discharge:	3.2 A to 1.0V	4.8 A to 1.0V	5.0 A s to 1.0V
Maximum intermittent discharge	4.8 A	7.2 A	7.5 A
Minimum charging cycles:	500	300	300
Average Weight:	28.0 g		
Recommended storage temperature:	5 – 20 °C		
Operating temperatures:	0 – 50 °C		
Terminals:	Flat contacts		
Jacket:	PVC Label		

Note:

- 1) No added Mercury / 99.9999% Mercury Free
- 2) No added Lead /99.999% Lead Free
- 3) No added Cadmium / 99.9999% Cadmium Free
- 4) No added PFOS (Perfluorooctane sulfonates)
- 5) This battery complies with ANSI C18, IEC 60086, and EU Directive 2006/66/EC, 2006/122/EC
- 6) Batteries are NOT subject to European RoHS regulations.
- 7) MSDS sheets are available on request from Strand Europe Ltd.
- 8) Charge or Discharge at extreme high or low temperature will significantly affect service and cycle life.
- 9) For best performance after long period of non-use, charge and discharge the battery several times.

